



PRODUCT INFORMATION SHEET

FIXED SOLUTIONS

Protecting uptime through floor-level contamination control.



Professional Installation



Static Dissipative



3-5 Year Lifespan

Long-term contamination control built into your facility

Dycem Fixed Solutions provide reliable contamination control for critical access points and transition areas. Scientifically proven to capture up to **99.9%** of shoe and wheel-borne contamination and reduce up to **75%** of airborne contamination at floor level.

Installed as a semi-permanent part of the facility, Fixed Solutions create a continuous contamination control zone that supports cleaner environments.



Reusable

Long-lasting contamination control that reduces waste and lowers total cost of ownership.



Sustainable

Sustainable alternative, reducing the need for single-use plastics and contaminated waste.



Easy to Use

Permanently installed for continuous protection. Simple cleaning and no daily replacement.

WHY CHOOSE DYCEM'S FIXED SOLUTIONS?



Customizable

Choose from a range of colors and sizes.



Easy to Clean

Integrate into existing procedures.



Compliant

Designed to support best-practice under ISO guidelines.



COMPLIANCE



MAT COLORS



Midnight



Slate



Green



Red



Cobalt



Titanium

EDGING COLORS



Available in a range of color, size and edging options.

TECHNICAL SPECIFICATIONS

SIZE	Nominal Thickness: 21 mm Width: 1.2 m or 2.0 m Length: Custom	CLEANING	Controlled manual clean. Cleaned according to facility specifications and Dycem SOP's.
WEIGHT	Nominal: 2.4 kg/m ²	TOXICITY	Non-toxic, silicon, latex and melamine-free, no known adverse skin reactions
SURFACE RESISTIVITY	10 ⁸ ohms (tested to ASTM F150, DIN 51953, BS 2050)	OFFGASSING	Requirements met for ISO 16000-3, ISO 16000-6, ISO 16000-9 and ISO 16000-11
LOAD RESISTANCE	Pedestrian and heavy wheeled traffic (70-90 kg/cm ²)	UV & HEAT RESISTANCE:	Working range 0-50° C. Constant exposure to light will degrade surface.
CO-EFFICIENT OF FRICTION	≥ 0.30 in accordance with EN 13893 - Technical class DS		
FLAMMABILITY	EFIS EN 14041:2004		

Protecting Uptime. **Protecting what matters.**

dycemdatacenters.com



Get in Touch